

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification<sup>6</sup> :

H04Q 7/32

A1

(11) International Publication Number:

WO 99/55105

(43) International Publication Date:

28 October 1999 (28.10.99)

(21) International Application Number: PCT/EP99/02578

(22) International Filing Date: 15 April 1999 (15.04.99)

(30) Priority Data:

9807967.6

16 April 1998 (16.04.98)

GB

(71) Applicant (for all designated States except US): MOTOROLA LIMITED [GB/GB]; Jays Close, Viabes Industrial Estate, Basingstoke, Hampshire RG22 4PD (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): HOWELL, Stephen, Andrew [GB/GB]; 56 Newstead Road, Barnwood, Gloucester GL4 3TQ (GB). BARNES, Nigel, Everard [GB/GB]; Tavy Cottage, Bishop's Sutton, Alresford SO24 0AL (GB).

(74) Agents: GIBSON, Sarah et al.; Motorola European Intellectual Property Operations, Midpoint, Alencon Link, Basingstoke RG21 7PL (GB).



(81) Designated States: CN, DE, US.

## Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: DATA CARRIER SYSTEM



## (57) Abstract

A cellular telephone (102) in a vehicle includes a data carrier system comprising a first semi-permanent Subscriber Identity Module (SIM) (200) selectively couplable to the cellular telephone (102) and a second SIM (300) selectively couplable to the cellular telephone (102) in preference to the first SIM (200), the first SIM (200) being arranged to be decoupled from the cellular telephone (102) when the second SIM (300) is coupled to the cellular telephone (102). During a predetermined period of time, the cellular telephone (102) is arranged to be ensured of a supply of power and the second SIM (300) is arranged to be decoupled from the cellular telephone (102), thereby causing the first SIM (200) to be coupled to the cellular telephone (102) for the execution of a task requiring the first SIM (200).

PTO/PCT Rec'd 12 OCT 2000

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon	KR	Republic of Korea	PL	Poland		
CN	China			PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

**DATA CARRIER SYSTEM**Field of the Invention

5 The present invention relates to a data carrier system, for example, of the type used by communications devices, such as cellular telephones. The present invention also relates to a method of operating the data carrier system.

10 Background of the Invention

It is known in some cellular telephony applications to install and activate a data carrier, such as a Subscriber Identity Module (SIM), in a cellular telephone so as to enable the cellular telephone to operate fully, otherwise a limited service is available. For example, in the Global System for Mobile communication (GSM), a SIM must be installed and activated in a GSM telephone in order to be able to use the GSM telephone, otherwise emergency calls may only be placed.

20 Less common, but still known in the art, is a cellular telephone having the capability of receiving two SIMs (a dual-SIM configuration): a semi-permanently installed SIM or fixed SIM having a first subscription associated therewith, and a visiting SIM having a second subscription associated therewith which may vary depending upon a user of the cellular telephone. The visiting SIM can be installed intermittently when required by the user. In such a configuration, even if both SIMs are electrically coupled to the cellular telephone, only one of the two SIMs is activated, since only one of the first and second subscriptions can be accepted by the network for any single cellular telephone. Therefore, the fixed SIM is usually disregarded or electrically decoupled from the cellular telephone when the visiting SIM is installed, the visiting SIM being activated in preference to the fixed SIM. The fixed SIM is thus not visible to the network.

35 When the visiting SIM is removed, the fixed SIM is activated and the first subscription becomes the active subscription in the network. If another, or the same visiting SIM is re-installed, the fixed SIM is deactivated and the first subscription not used; the new or the same visiting SIM and associated

second or other subscription becomes active. Generally, since the visiting SIM has priority over the fixed SIM, if the visiting SIM is never removed, the fixed SIM is never activated.

- 5 Applications are emerging for cellular telephones integrated into vehicles in order to add functionality to security or safety features of the vehicle. However, in order for such security or safety features to be efficient and effective, data stored on the fixed SIM must be accurate and up-to-date.
- 10 In the above described dual-SIM configuration, this is not realistically achieved, since it is not possible to guarantee that the fixed SIM can be kept up-to-date because of the possibility that the fixed SIM may never communicate with the network for a prolonged period of time. It is therefore an object of the present invention to provide a data carrier system which
- 15 obviates or mitigates the above described problem.

#### Summary of the Invention

- 20 According to the present invention, there is provided a data carrier system comprising a first data carrier selectively couplable to a communications device and a second data carrier selectively couplable to the communications device in preference to the first data carrier, the first data carrier being arranged to be decoupled from the communications device when the second
- 25 data carrier is coupled to the communications device; and during a predetermined period of time the communications device is arranged to be ensured of a supply of power and the second data carrier is arranged to be decoupled from the communications device, thereby causing the first data carrier to be coupled to the communications device for the execution of a task requiring the first data carrier.

- 30 According to the present invention, there is also provided a method of operating a data carrier system including a first data carrier selectively couplable to a communications device and a second data carrier selectively couplable to the communications device in preference to the first data
- 35 carrier, the first data carrier being arranged to be decoupled from the communications device when the second data carrier is coupled to the communications device, the method comprising the steps of: during a

predetermined period of time, ensuring a supply of power to the communications device, and decoupling the second data carrier from the communications device, thereby causing the first data carrier to be coupled to the communications device for the execution of a task requiring the first data carrier.

It is thus possible to provide a system and method for updating the first data carrier.

Other, preferred, features and advantages will become apparent from the accompanying description, drawings and dependent claims.

### Brief Description of the Drawings

At least one embodiment of the invention will not be described, by way or example, with reference to the accompanying drawings, in which:

FIG. 1 is a schematic illustration of an automobile in the vicinity of a base station of a cellular telephone network;

FIGs. 2 and 3 are schematic diagrams of apparatus constituting an embodiment of the invention;

FIGs. 4 to 6 are flow diagrams of a method of operation of the apparatus of FIGs. 2 and 3 in one embodiment of the invention, and

FIGs. 7 to 11 are flow diagrams of another method of operation of the apparatus of FIGs. 2 and 3 in another embodiment of the invention.

### Description of a Preferred Embodiment

A vehicle, such as an automobile 100, includes a cellular telephone 102, such as a GSM International 2000 cellular telephone manufactured by Motorola Electronic GmbH electrically connected to a trunk unit 104 having a first SIM card reading unit 214 (FIG. 2), typically located in the boot (sometimes referred to as the 'trunk') of the automobile 100. The cellular telephone 102

(FIG. 1) is electrically connected (not shown) to an antenna 106 for communication with a base station 108 of a GSM cellular telephone network, via a radio interface 110.

5 The first SIM card reading unit 214 receives and holds, on a semi-permanent basis, a first SIM card 200 (hereinafter referred to as the "fixed SIM"). Referring to FIG. 3, the cellular telephone 102 has a second SIM card reading unit 304 for reading a second SIM card 300 (hereinafter referred to as the "visiting" SIM) and a keypad 306 comprising an on/off key 308 for  
10 powering-up and powering-down the cellular telephone 102. By "power-down" (or "unpower"), it is meant that the cellular telephone 102 enters a "stand-by" mode where a keypad of the cellular telephone 102 is disabled, a display of the cellular telephone 102 is switched off, and any indication of the cellular telephone 102 being in service is removed, i.e. there is no indication  
15 to a user that the cellular telephone 102 is active. The second SIM card reading unit 304 receives, through a slot 302, the visiting SIM 300 on a permanent or temporary basis.

The first or second SIM card 200, 300 can be contactless smartcards.

20

It should be noted that it is also conceivable to locate the second SIM card reading unit 304 elsewhere in the automobile 100 which is accessible to a user.

25 The trunk unit 104 (FIG. 2) comprises a microcontroller 202 having a first terminal 204, a second terminal 206, a third terminal 208, and a fourth terminal 212, the first terminal 204 being connected to an accident detection unit 205, for example, a sensor for detecting the deployment on an airbag. The second terminal 206 is connected to a Global Positioning System (GPS)  
30 receiver 210 for the determination of a location of the automobile 100. The third terminal 208 is connected to other interfaces, for example, coupled to a security unit 209 for managing the security of the automobile 100. Additionally, or alternatively, the other interfaces can be coupled to a key, button or switch acting as a "panic button" 211 (hereinafter referred to as  
35 the panic button). The fourth terminal 212 is connected to the cellular telephone 102 located in a cabin of the automobile 100.

The second SIM card reading unit 214 is also connected to the cellular telephone 102 via a switch 216, the switch 216 being under the control of the microcontroller 202 and connected to a fifth terminal 218 of the microcontroller 202.

5

In each embodiment of the invention, electrical connection and activation of the fixed SIM 200 is required in order to execute a task. The task can be to update data stored by the fixed SIM 200 relating to addresses to be automatically contacted in emergency or other situations, such as upon  
10 compromise of the security of the automobile 100. In the event of an accident or other emergency, the emergency services need to be contacted. Also, it can be desirable to collect and/or transmit information relating to the performance of the automobile 100. In the event of the security of the automobile 100 being compromised, the security services/the police need to  
15 be contacted.

During normal operation, examples embodiments of the invention function as follows.

20 Referring to FIG. 4, the cellular telephone 102 polls the keypad 306 in order to determine (step 400) when the user has pressed the on/off key 308 in order to power-down the cellular telephone 102 into stand-by mode. When actuation of the on/off key 308 has been detected (step 400), the cellular telephone 102 executes (step 402) an update routine 500 (FIG. 5) for the  
25 fixed SIM 200.

The update routine 500 includes the following steps. The cellular telephone 102 determines (step 502) whether the visiting SIM 300 has been installed. If the visiting SIM 300 has been detected as installed, the visiting SIM 300 is  
30 electrically disconnected or ignored (step 504), and the fixed SIM 200 is electrically connected (step 506) and enabled (step 508). This can be achieved by the cellular telephone 102 instructing the microprocessor 202 to actuate the switch 216 through the fifth terminal 218. If the cellular telephone 102 determines (step 502) that the visiting SIM 300 is not  
35 installed, the fixed SIM 200 is activated (step 506) without disconnecting (step 504) the visiting SIM 300 and connecting (step 506) the fixed SIM 200; this is because, in the absence of the visiting SIM 300, the system typically

automatically defaults to the connection and activation of the fixed SIM 200. A GSM dialogue (step 510) is then initiated. The dialogue can be the transmission and/or receipt of a Short Messaging Service (SMS) message, a telephone call involving the transmission of data or any other form of dialogue known in the art for the purpose of updating the fixed SIM 200. The data to be updated can be data relating to addresses described above. Once the dialogue has been completed, an inactivity timer (not shown) is initiated (step 512) for the purpose of powering-up the cellular telephone at a predetermined interval, for example, every day, week, or month, in order to update the fixed SIM 200. The update routine 500 then terminates and (FIG. 4) the cellular telephone is permitted to power-down (step 404).

In a further example (FIG. 6), the cellular telephone 102 monitors the inactivity timer and determines (step 600) when the predetermined interval has expired. When the predetermined interval has expired, the cellular telephone 102 powers-up (step 602) automatically (i.e. without intervention by the user) and executes (step 604) the update routine 500 (FIG. 5) for the fixed SIM 200 described above. Once the update routine 500 has been executed, the cellular telephone 102 powers-down (step 606).

In an example of another embodiment (FIG. 7), the accident detection unit 205 monitors the sensors to determine (step 700) whether an accident has occurred, for example the detection of deployment of the airbag. If the accident has been detected, the cellular telephone 102 executes (step 702) a contact routine 800 (FIG. 8). The contact routine includes the following steps.

The cellular telephone 102 determines (step 802) whether the visiting SIM 300 is installed and activated. If the visiting SIM 300 is installed and activated, the cellular telephone 102 electrically disconnects or ignores (step 804) the visiting SIM 300 and electrically connects (step 806) the fixed SIM 200. The fixed SIM 200 is then activated (step 808). If the cellular telephone determines (step 802) that the visiting SIM 300 is not installed or activated, the fixed SIM 200 is activated without disconnecting (step 804) the visiting SIM 300 and connecting (step 806) the fixed SIM 200. The cellular telephone 102 then communicates (step 810) with an appropriate service, for example the police and/or ambulance service, by data



communication, such as SMS, or voice communication, such as a pre-recorded message. The contact routine 800 then terminates and the cellular telephone 102 proceeds to reconnect (step 704) and activate any visiting SIM 300 installed in the cellular telephone 102.

5

In another example of this embodiment (FIG. 9), the cellular telephone 102 monitors (step 900) the other interfaces, via the microcontroller 202, for the actuation of the panic button 211. When the cellular telephone detects that the panic button has been actuated, the cellular telephone 102 executes (step 902) the contact routine 800 described above. However, in this case the appropriate service contacted (step 810) is the police. Once a message has been sent to the police, the cellular telephone 102 reconnects (step 904) any visiting SIM 300 installed in the cellular telephone 102.

15 In a further example of this embodiment (FIG. 10), the cellular telephone 102 polls the security unit 209 in order to determine (step 1002) whether an unauthorised party is tampering with the automobile 100 or whether the automobile 100 has been stolen. If any of the above conditions have been detected (step 1002), the cellular telephone 102 executes (step 1004) the contact routine 800. Again, the appropriate service contacted (step 810) can be the police or a security company which monitors the security of the automobile 100. Whilst contacting the police or the security company, the cellular telephone 102 receives position data relating to the location of the automobile 100 from the GPS receiver 210 and communicates the position data to the police and/or the security service. Once the contact routine 800 has terminated, the cellular telephone 102 ensures (step 1006) that the fixed SIM 200 remains electrically connected and activated so as to communicate updated position data, if necessary.

30 In another example of the above embodiment (FIG. 11), the cellular telephone 102 receives (step 1102) data from a sensor connected to the odometer. At a second predetermined interval (which can be the same as the first predetermined interval), the cellular telephone 102 then executes (step 1104) the contact routine 800. In this example, the cellular telephone 102 contacts the manufacturer of the automobile 100 or a garage responsible for maintenance of the automobile 100, and communicates the odometer reading to the manufacturer or the garage. Once the contact routine 800 has

35

terminated, the cellular telephone 102 reconnects (step 1106) and activates any visiting SIM 300 installed in the cellular telephone 102.

5 Such a procedure as described above can be executed whilst the cellular telephone 102 is powered-up, or alternatively, whilst the cellular telephone 102 is powered-down or upon initial powering-up of the cellular telephone 102 so as to minimise delay to the user in using the cellular telephone 102.

10 It is conceivable that in addition to or instead of the odometer reading other information can be communicated to the manufacturer or the garage, for example, details of faults detected by an engine management system or other sensors.

## Claims

1. A data carrier system comprising a first data carrier selectively couplable to a communications device and a second data carrier selectively couplable to the  
5 communications device in preference to the first data carrier, the first data carrier being arranged to be decoupled from the communications device when the second data carrier is coupled to the communications device; and during a predetermined period of time the communications device is arranged to be ensured of a supply of power and the second data carrier is arranged to be decoupled from the  
10 communications device, thereby causing the first data carrier to be coupled to the communications device for the execution of a task requiring the first data carrier.
2. A system as claimed in Claim 1, wherein during substantially at least the predetermined period of time the communications device is arranged to be ensured of  
15 the supply of power by maintaining the supply of power to the communications device in response to a command to extinguish the supply of power to the communications device, thereby facilitating execution of the task requiring the first data carrier.
- 20 3. A system as claimed in claim 1, wherein the communications device is actuatable between a powered state and an unpowered state, the communications device being arranged to be actuated from the unpowered state to the powered state at a predetermined interval for substantially at least the predetermined period of time.
- 25 4. A system as claimed in any one of the preceding claims, further comprising means for receiving the first data carrier, wherein the first data carrier is arranged to be substantially permanently in engagement with the means for receiving the first data carrier.
- 30 5. A cellular telephone comprising the system as claimed in anyone of the preceding claims.

6. A vehicle comprising the system as claimed in any preceding claim.
7. A method of operating a data carrier system including a first data carrier selectively couplable to a communications device and a second data carrier--
- 5 selectively couplable to the communications device in preference to the first data carrier, the first data carrier being arranged to be decoupled from the communications device when the second data carrier is coupled to the communications device, the method comprising the steps of:
- 10 during a predetermined period of time, ensuring a supply of power to the communications device, and
- decoupling the second data carrier from the communications device, thereby causing the first data carrier to be coupled to the communications device for the execution of a task requiring the first data carrier.
- 15 8. A method as claimed in Claim 7, further comprising, during substantially at least the predetermined period of time, ensuring the supply of power by maintaining the supply of power to the communications device in response to a command to extinguish the supply of power to the communications device, thereby facilitating execution of the task requiring the first data carrier.
- 20 9. A method as claimed in Claim 7, wherein the communications device is actuatable between a powered state and an unpowered state, and further comprises actuating the communications device from the unpowered state to the powered state at a predetermined interval for substantially at least the predetermined period of time.
- 25 10. A method as claimed in any one of claims 7 to 9, further comprising providing means for receiving the first data carrier, and substantially permanently engaging the first data carrier with the means for receiving the first data carrier.
- 30 11. A method or system as claimed in any preceding claim, wherein the first data carrier is a smartcard.

12. A method or system as claimed in any preceding claim wherein the second data carrier is a smartcard.

13. A method or system as claimed in Claim 11 or Claim 12, wherein the smartcard is a contactless smartcard.

14. A method or system as claimed in claims 11, 12 or 13 wherein the smartcard is a Subscriber Identity Module.

15. A method or system as claimed in any preceding claim further comprising providing location determining means.

16. A method as claimed in Claim 15, wherein the location determining means is a Global Positioning System receiver.



17. A method or system as claimed in any preceding claim, wherein the task is to update data stored in the first data carrier using the communications device.

18. A method or system as claimed in claim 17 wherein the data to be updated includes addresses to be used in conjunction with vehicle applications.

19. A method or system as claimed in claim 18 wherein the vehicle applications include one or both of security call and emergency call applications.



This Page Blank (uspto)

1 / 4



529 Rec'd PCT/PTO 12 OCT 2000



**FIG. 3****FIG. 4****FIG. 5**

529 Rec'd PCT/PTC 12 OCT 2000

3 / 4




FIG. 6




FIG. 7




FIG. 8

529 Rec'd PCT/PTC 12 OCT 2000

4 / 4




FIG. 9




FIG. 10




FIG. 11

529 Rec'd PCT/PTC 12 OCT 2000

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 99/02578

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 6 H04Q7/32

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P, X	WO 98 33343 A (TELECOM FINLAND) 30 July 1998 (1998-07-30)	1, 4, 5, 7, 10-14, 17
P, Y	page 7, line 15 - page 11, line 35; figures	15
P, Y	WO 98 24257 A (NOKIA) 4 June 1998 (1998-06-04)	15
P, X	WO 98 27767 A (NOKIA) 25 June 1998 (1998-06-25)	1, 7, 11-14
Y	WO 97 25828 A (ERICSSON) 17 July 1997 (1997-07-17)	1, 7
A	page 10, line 25 - page 25, line 13; figures	2-6, 8-14
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

3 August 1999

Date of mailing of the international search report

30. 09. 1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.  
Fax: (+31-70) 340-3016

Authorized officer

Geoghegan, C

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 99/02578

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 0 562 890 A (HUTCHISON MICROTEL) 29 September 1993 (1993-09-29) page 2, column 2, line 33 - page 4, column 6, line 58; figures ---	1,7
A	WO 97 26719 A (NEWCOM TECHNOLOGIES) 24 July 1997 (1997-07-24) page 7, line 17 - page 12, line 27; figures ---	1,7
A	WO 97 05729 A (TELECOM ITALIA MOBILE) 13 February 1997 (1997-02-13) page 2, line 17 - page 5, line 16 -----	1,7



# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 99/02578

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9833343 A	30-07-1998	FI 970339 A AU 5865998 A	28-07-1998 18-08-1998
WO 9824257 A	04-06-1998	FI 964732 A AU 5122598 A	28-05-1998 22-06-1998
WO 9827767 A	25-06-1998	FI 965071 A AU 5399098 A	18-06-1998 15-07-1998
WO 9725828 A	17-07-1997	AU 1325597 A	01-08-1997
EP 562890 A	29-09-1993	NONE	
WO 9726719 A	24-07-1997	AU 1064697 A AU 697560 B AU 7533496 A CN 1214162 A EP 0785634 A	11-08-1997 08-10-1998 24-07-1997 14-04-1999 23-07-1997
WO 9705729 A	13-02-1997	IT RM950521 A AU 6667896 A BG 102267 A CA 2227340 A CN 1192308 A CZ 9800233 A EP 0840973 A HU 9900175 A NO 980341 A NZ 315079 A PL 324646 A	27-01-1997 26-02-1997 30-12-1998 13-02-1997 02-09-1998 15-07-1998 13-05-1998 28-04-1999 26-03-1998 28-01-1999 08-06-1998

This Page Blank (uspto)